

AVAILABLE MOUNTING CONFIGURATIONS

8STX-F FRAME MOUNT
8STX-EM ENGINE MOUNT

OPERATING LEVELS

MIN FLOW	290 GPM	66.7 m ³ /h
MAX FLOW	2880 GPM	662.4 m ³ /h
DISCHARGE SIZE	8"	200 mm
SUCTION SIZE	8"	200 mm
SOLIDS HANDLING	3"	7.6 mm
MAX SPEED	1800 RPM	1800 RPM
SHUT-OFF HEAD	216'	65.8 m
BEP HEAD	146'	44.5 m
BEP FLOW	2260 GPM	513.3 m ³ /h
BEP PERCENT	67%	67%



A typical picture of the pump is shown. Please contact InterTech Pump Company for further details. All information is approximate and for general guidance only.

InterTech's self-priming pump, with industry-leading efficiency, runs several percentage points higher than other manufacturers. Features patented Cycloseal® backplate and uniquely designed volute for best performance, with a 8" suction and 8" discharge.

PARTS	STANDARD MATERIAL (ALL IRON)
VOLUTE CASING	DUCTILE IRON
IMPELLER	DUCTILE IRON
IMPELLER SCREW	304 STAINLESS STEEL
BACKPLATE/BACKET	DUCTILE IRON
WEAR PLATE	CAST IRON
BEARING FRAME	DUCTILE IRON
SHAFT	17-4 PH STAINLESS STEEL
SHAFT SLEEVE	416 STAINLESS STEEL
FASTENERS	GRADE 5 STEEL
MECHANICAL SEAL	SILICON CARBIDE VS. SILICON CARBIDE, TYPE 2

- Available with ANSI or DIN flanges & frame or engine mount
- Optional self-cleaning wear plate
- Modular bearing frame
- InterTech's Cycloseal® with type 2 seal
- Dual protection of bearings with external seal leakage monitor (vent to atmosphere)
- Retrofit-able with existing installations
- High-efficiency design
- Oversized oil reservoir for better cooling
- Replaceable shaft sleeve
- Heavy-duty ductile iron construction
- Designed for SAE conversion
- High RPM Capability
- FIVE-YEAR warranty



AGRICULTURE



FOOD



INDUSTRIAL



MINING



MUNICIPAL



OIL & GAS



REFRIGERATION



RENTAL

